



WOLLE

# WOLLE P1500

Semi-rigid thermal insulation fibre boards — 10 cm thickness, 5.856 m<sup>2</sup> pack

## TO BE COMPLETED AT THE TIME OF SALE

CUSTOMER

PROJECT (SITE ADDRESS)

PURCHASE DOCUMENT (SERIES / NUMBER)

DATE OF PURCHASE

QUANTITY

PRODUCTION BATCH

APPLICATION (AS PER THE TABLE BELOW)

### Statutory guarantee of conformity

Applies unconditionally, under the mandatory law of the country of sale. This certificate does not limit those rights.

### 50 years

Extended commercial guarantee, granted voluntarily by Isofect Insulation in addition to the buyer's statutory rights, on the terms of this certificate.

## COVERED APPLICATIONS AND THE DURATION OF THE EXTENDED WARRANTY

| APPLICATION                                                                                                                                                                                                                                     | EXTENDED WARRANTY                                                 |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| Installation inside the building envelope, in closed, protected structures, without exposure to the weather, to ultraviolet radiation or to permanent contact with water — attics, walls, beam floors, partition walls and similar applications | <b>50 years</b>                                                   |
| Any other application, outside the field of use declared in the technical data sheet                                                                                                                                                            | <b>No extended guarantee; the buyer's statutory rights remain</b> |

## WHAT THE EXTENDED WARRANTY COVERS

Isofect Insulation supplies replacement product free of charge for the affected area, in the same quantity, throughout the warranty period and without reduction over time. Coverage is not reduced according to the age of the product and is not conditional on any contribution from the customer. The warranty does not include the labour of removal and reinstallation.

## WARRANTED PARAMETERS

Isofect Insulation warrants that the product does not break down — the fibres retain their integrity, without crumbling, powdering or loss of cohesion of the board — and that it does not settle beyond the class declared under EN 15101-1. The remedy, at Isofect Insulation's choice: replacement with the product or payment of its value, reduced pro rata by 3.33 % for each year commenced after the twentieth year from purchase.

Isofect Insulation S.R.L. — signature and stamp

Customer — name, signature, date

**S.C. ISO FLECT INSULATION S.R.L.**

CIF RO30340616 · Reg. com. J2012000359286

Șos. Caragea Vodă nr. 89A, Domnești, sat Țegheș, jud. Ilfov

**Warehouse and deliveries**

ELI Park 3, secțiunea S10, Str. Speranței 101, Buftea, Ilfov  
+40 21 780 7585 · WhatsApp 0790 644 051 · contact@isoflect.ro



## 1. GENERAL PROVISIONS

1. The warranty runs from the date of purchase and is proven by the purchase documents.
2. The statutory guarantee of conformity applies under the mandatory law of the country of sale and is not restricted by this certificate.
3. The extended commercial guarantee is a voluntary undertaking by Isoflect Insulation, in addition to the buyer's statutory rights, granted on the terms set out in point 2.
4. The extended warranty transfers with the building, to subsequent owners, without any formality.

## 2. CONDITIONS FOR GRANTING THE EXTENDED WARRANTY

1. Presentation of the purchase document. The product must have been bought for own use, not for resale.
2. Installation carried out by qualified personnel, in accordance with the product's technical data sheet in the revision in force at the date of installation and within the field of use declared therein; stricter national regulations are also observed, where they exist.
3. Sealing of joints and overlaps exclusively with Isoflect Power Tape and use exclusively of Isoflect system accessories.
4. Registration of the project on [isoflect.ro](http://isoflect.ro) within no more than 90 days from the date of purchase. Failing registration, the extended warranty is granted for 10 years.
5. Installation within no more than 3 months from the date of delivery, with storage in accordance with the technical data sheet.
6. The assembly must not be altered subsequently by renovation or additional works affecting the product, without the written consent of Isoflect Insulation.
7. Notification of Isoflect Insulation within no more than 30 days from discovery of the problem, with access to the site being provided for inspection.

## 3. SITUATIONS THAT DO NOT CONSTITUTE A NON-CONFORMITY

- Installation outside the field of use declared in the technical data sheet.
- Mechanical damage after delivery — cuts, perforations, improper fastening.
- Exposure to ultraviolet radiation beyond the declared period, before covering with the final layer.
- Permanent contact with water or installation under immersion.
- Damage caused by other materials installed in contact with the product — adhesives, wood protection solutions, expanding foams, mortars or wet screeds in direct contact with the metal face.
- Contact with chemical or corrosive agents, in liquid, vapour or condensate form — including alkaline, acidic or chloride-bearing environments — and direct contact with dissimilar metals in the presence of moisture.
- Exposure to temperatures outside the limits declared in the technical data sheet, permanent or repeated.
- Movement or settlement of the building structure.
- Assemblies without hygrothermal verification or with insufficient ventilation of the air space.
- Changes of colour, staining, normal wear and other visual effects that do not influence the declared performance.
- Unsuitable installation substrate or one not in accordance with the design.
- Force majeure — lightning, storm, hail, earthquake, flood — vandalism and indirect damage.

## 4. EXCLUSIONS FROM THE EXTENDED WARRANTY

Beyond the situations under point 3, which concern both the legal guarantee and the extended one, the extended commercial warranty is not granted, or ceases, in the following cases:

- sealing of joints or overlaps with tapes other than Isoflect Power Tape;
- failure to register the project within the term under point 2.4 — the extended warranty remains 10 years;
- installation more than 3 months after the date of delivery, or storage in conditions other than those in the technical data sheet;
- inability to present the purchase document or this certificate duly filled in;
- removal and reinstallation of the product, or its relocation to another project;
- alteration of the assembly after installation, without the written consent of Isoflect Insulation;
- products from which the identification marking or the production batch has been removed;
- refusal of access to the site for inspection of the complaint.

The extended warranty covers exclusively the replacement product. It does not cover the labour of removal and reinstallation, energy costs, loss of use, finishing works affected by the intervention, nor any other indirect damage.

## 5. COMPLAINT PROCEDURE

The complaint is sent to [contact@isoflect.ro](mailto:contact@isoflect.ro), accompanied by this certificate, by the purchase document and by photographs of the affected area. Isoflect Insulation replies within no more than 15 working days and arranges, where appropriate, an inspection on site.

## 6. SERVICE LIFE AND THE BASIS OF THE DECLARATION

Expected service life in the works: **over 100 years, when installed inside the building envelope.**

Polyester fibre is not hygroscopic, and the boards are thermally bonded, without organic binder. The only degradation path for polyester is hydrolysis, which requires high heat and high humidity at the same time; inside the building envelope, at normal service temperatures and humidities, the rate of the process is negligible.